



# DCP FireMate FIRE EXTINGUISHERS

Firemate's range of stored pressure dry chemical powder extinguishers is suitable for A, B or C class fires or a combination of ABC class fires. All the extinguishers supplied conform to the minimum fire ratings as specified in SANS 1910:2009. Dry chemical powders have been developed over a period of thirty years and can be supplied as Alpha Dynaflo (SABS grade 3A/5B) an ultra-high performance product or in various grades down to our Alpha Megaflo which carries a 2A/2B rating. The powders are siliconised for superior flow and anti-caking.

## SANS 1910:2009 CERTIFIED



DCPCOMFF0.6

**0.6kg**  
DCP  
FIREMATE

The 0.6kg is the smallest extinguisher in our range, classified as disposable and conforms to:



DCPCOMFF1

**1.0kg**  
DCP  
FIREMATE

The 1kg extinguisher is suitable for Class A, B or C fires or combination and ideal for home use.



DCPCOMFF1.5

**1.5kg**  
DCP  
FIREMATE

The 1.5kg is the ideal extinguisher for the motor racing industry and fire protection in your motor.



DCPCOMFF2.5

**2.5kg**  
DCP  
FIREMATE

The 2.5kg is highly effective fire extinguisher that provides rapid fire knock down. Suitable for offices and factories.



DCPCOMFF4.5

DCPCOMFF9

**4.5kg**  
DCP  
FIREMATE

The 4.5kg extinguisher is fitted with a high pressure discharge hose and discharge nozzle.

**9kg**  
DCP  
FIREMATE

The 9kg extinguishers is the largest fire extinguisher in the Firemate range and suitable for big fires.

### SANS1322

**FIRE RATING**  
3A/8B

#### Specifications:

**Height:** 285mm  
**Diameter:** 68mm  
**Mass empty:** 0.6kg  
**Mass full:** 1.2kg  
**Discharge:** >6sec  
**Working pressure:** 1400kPa  
**Test pressure:** 2100kPa  
**Burst pressure:** >5500kPa  
**Safety valve:** none

**FIRE RATING**  
5A/21B

#### Specifications:

**Height:** 330mm  
**Diameter:** 80mm  
**Mass empty:** 0.8kg  
**Mass full:** 1.8kg  
**Discharge:** >6sec  
**Working pressure:** 1400kPa  
**Test pressure:** 2100kPa  
**Burst pressure:** >5500kPa  
**Safety valve:** +/- 2200kPa

**FIRE RATING**  
5A/34B

#### Specifications:

**Height:** 360mm  
**Diameter:** 110mm  
**Mass empty:** 1.3kg  
**Mass full:** 2.8kg  
**Discharge:** >6sec  
**Working pressure:** 1400kPa  
**Burst pressure:** >5500kPa  
**Test pressure:** 2100kPa  
**Safety valve:** +/- 2200kPa

**FIRE RATING**  
8A/55B

#### Specifications:

**Height:** 415mm  
**Diameter:** 110mm  
**Mass empty:** 1.4kg  
**Mass full:** 3.9kg  
**Discharge:** >6sec  
**Working pressure:** 1400kPa  
**Test pressure:** 2100kPa  
**Burst pressure:** >5500kPa  
**Safety valve:** +/- 2200kPa

**FIRE RATING**  
21A/89B

#### Specifications:

**Height:** 420mm  
**Diameter:** 175mm  
**Mass empty:** 3.0kg  
**Mass full:** 7.5kg  
**Discharge:** >9sec  
**Working pressure:** 1400kPa  
**Test pressure:** 2100kPa  
**Burst pressure:** >5500kPa  
**Safety valve:** +/- 2200kPa

**FIRE RATING**  
27A/144B

#### Specifications:

**Height:** 580mm  
**Diameter:** 175mm  
**Mass empty:** 3.9kg  
**Mass full:** 12.9kg  
**Discharge:** >12sec  
**Working pressure:** 1400kPa  
**Test pressure:** 2100kPa  
**Burst pressure:** >5500kPa  
**Safety valve:** +/- 2200kPa

