



# MOBILE FIRE PROTECTION AND WATER TRANSFER

Safequip has a broad selection of veld firefighting equipment, with the most popular product being the Fire King mobile firefighting unit. Safequip specialises in manufacturing skid units and offers a variety of products to suit every clients individual needs.

**Protect your property with SA's No.1 firefighter.**



QBBU008  
**500L TANK**

## LOW PRESSURE Economy Skid Unit

The Low Pressure Economy Skid Unit has a suction hose and strainer of 5 meter with an excellent spray reach of 18 meter.

### Specifications:

**Pump:** ZB50  
**Pump Flow Rate:** 416lpm  
**Total Head/Bar:** 2.5 Bar  
**Engine:** Akira  
**Engine Capacity:** 5.5hp  
**Tank Capacity:** 500 Litres  
 Plastic T-style Tank  
**Baffle Plates:** N.A.  
**Suction Diameter:** 5m/ 40mm  
**Hose Outlets:** 1 hose outlet  
**Hose Length:** 10m  
**Hose Type:** Drag line SABS 10 bar  
**Spray Reach:** <=18m  
**Applications:** Able to switch between applications while engine is running  
**Branch Pipe/Nozzle:** Chinese Mini Jet Spray Nozzle



QBBU005  
**500L TANK**

## HIGH PRESSURE Economy Skid Unit

The High Pressure Economy Skid Unit weighs only 65kg and has an automatic unloader valve that regulates pressure.

### Specifications:

**Pump:** Ruby TR-22AG  
**Pump Flow Rate:** 17-20lpm  
**Total Head/Bar:** 35 Bar  
**Engine:** Honda GX160  
**Engine Capacity:** 5.5hp  
**Tank Capacity:** 500 Litres  
 Plastic T-style Tank  
**Baffle Plates:** N.A.  
**Suction Diameter:** N.A.  
**Hose Outlets:** 2 Hose outlets max  
**Hose Length:** 10m  
**Hose Type:** Hydraulic Hose  
**Spray Reach:** <=7m  
**Applications:** Pump can run dry without damaging seals  
**Branch Pipe/Nozzle:** High pressure trigger gun



DAVPBU1650H160

## SINGLE IMPELLER Skid Unit

The Single Impeller Skid Unit is a dependable water solution for fire protection and water transfer with a 30m delivery hose. Best suited for a medium volume application.

### Specifications:

**Pump:** Davey 5/8" Single Stage Firefighter  
**Pump Flow Rate:** 500lpm  
**Total Head/Bar:** 7 Bar  
**Engine:** Honda GX160  
**Engine Capacity:** 5.5hp  
**Tank Capacity:** 650 Litres  
 Plastic Step Tank  
**Baffle Plates:** N.A.  
**Suction Diameter:** 5m/40mm  
**Hose Outlets:** 3 outlets (hose reel incl.)  
**Hose Length:** 30m  
**Hose Type:** Drag Line SABS 10 bar  
**Spray Reach:** <=20m  
**Applications:** Able to switch between applications while engine is running  
**Branch Pipe/Nozzle:** German designed AWG mini jet/spray nozzle



DAVDBU2700H160

## TWIN IMPELLER Skid Unit

The Twin Impeller Skid Unit includes a 60m delivery hose and a 5m suction hose assembly that is ideal for high volume application. The unit includes quick coupling on suction.

### Specifications:

**Pump:** Davey 5/8" Twin Stage Firefighter  
**Pump Flow Rate:** 400lpm  
**Total Head/Bar:** 10 Bar  
**Engine:** Honda GX160  
**Engine Capacity:** 5.5hp  
**Tank Capacity:** 700 Litres  
 Fibre Glass Tank  
**Baffle Plates:** Yes  
**Suction Diameter:** 5m/ 40mm  
**Hose Outlets:** 3 outlets (hose reel incl.)  
**Hose Length:** 60m  
**Hose Type:** Drag Line SABS 10 bar  
**Spray Reach:** <=20m  
**Applications:** Able to switch between applications while engine is running  
**Branch Pipe/Nozzle:** German designed AWG mini jet/spray nozzle

**You can't afford to wait in an emergency**



Experts in water.



Experts in water.

**These units can also be used for animal dipping, cleaning & washing of farm equipment, stables and many other.**